



7213BG Bearing 2D drawings and 3D CAD models

65,000 mm x 120,000 mm x 23,000 mm NTN
7213BG angular contact ball bearings

Bearing No. 7213BG

Size	65x120x23 mm
Bore Diameter	65,000 mm
Outer Diameter	120,000 mm
Width	23,000 mm
d	65,000 mm
D	120,000 mm
B	23,000 mm
C	23,000 mm
a	50.5 mm
Contact angle	40 °
rs min	1.5 mm
r1s min	1 mm
Radial clearance class	CN
Mass	0.98 kg
Dynamic load, C	63.5 kN
Static load, C0	52.5 kN
Fatigue limit load, Cu	3.6 kN
Nlim (oil)	7,000 rpm
Nlim (grease)	5,200 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C
da min	73.5 mm
db min	70.5 mm
Da max	111.5 mm



BEARINGS IMPORTED AND EXPORTED CO.,LTD.

Db max	114.5 mm
r1a max	1 mm
ra max	1 mm
Category	Angular Contact Ball Bearings
Inventory	2.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	1.03
EAN	4547359443684
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric
Long Description	65MM Bore; 120MM Outside Diameter; 23MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring
Category	Angular Contact Ball Bearing
UNSPSC	31171531



BEARINGS IMPORTED AND EXPORTED CO.,LTD.

Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	7213BG
Weight / LBS	2.276
Width	0.906 Inch 23 Millimeter
Outside Diameter	4.724 Inch 120 Millimeter
Bore	2.559 Inch 65 Millimeter
bore diameter:	65 mm
radial static load capacity:	52500 N
outside diameter:	120 mm
operating temperature range:	-40 to 120 ° C
overall width:	23 mm
cage material:	Steel
contact angle:	40 °
maximum rpm:	7000 rpm
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
bore type:	Round
precision rating:	ISO Class 0
closure type:	Open
fillet radius:	1.5 mm
snap ring included:	Without Snap Ring
weight:	1.030 kg
bearing material:	High Carbon Chrome Steel
manufacturer product page:	Click here
radial dynamic load capacity:	63500 N