



BEARINGS IMPORTED AND EXPORTED CO.,LTD.



629X50LLB Bearing 2D drawings and 3D CAD models

9,000 mm x 26,000 mm x 8,000 mm NTN
629X50LLB deep groove ball bearings

Bearing No. 629X50LLB

Size	9x26x8 mm
Bore Diameter	9,000 mm
Outer Diameter	26,000 mm
Width	8,000 mm
d	9,000 mm
D	26,000 mm
B	8,000 mm
C	8,000 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.019
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	9MM Bore; 26MM Outside



BEARINGS IMPORTED AND EXPORTED CO.,LTD.

	Diameter; 8MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage; No
Other Features	Deep Groove Non-Friction Nitrile Rubber Seal
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	1.024 Inch 26 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.315 Inch 8 Millimeter
Bore	0.354 Inch 9 Millimeter
bore diameter:	9 mm
static load capacity:	1960 N
outside diameter:	26 mm
precision rating:	ISO Class 0
overall width:	8 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Sealed
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	8 mm
snap ring included:	Without Snap Ring
outer ring width:	8 mm
internal clearance:	CN



BEARINGS IMPORTED AND EXPORTED CO.,LTD.

maximum rpm (grease):	30000 rpm
operating temperature range:	-40 to 120 ° C
fillet radius:	0.6 mm
dynamic load capacity:	4550 N
manufacturer product page:	Click here